



Maximise the benefits of automated cleaning tools

6th April 2020 | Louise Smyth



To meet application-specific requirements, design engineers in industries that manufacture sensitive components often need more flexibility than standard options allow for automating wet process cleaning equipment.

These specialised components can range from chips, wafers, semiconductors and electronic devices to the specialised optics for world-class lasers. In fact, the more complex the equipment, the greater the need becomes for more advanced adaptable cleaning options.



Cleaning, an integral part of many manufacturing and maintenance processes, is often critical to the performance of a broad range of technologies and refers to the use of agents such as solvents, acids or bases to remove unwanted particulates and other contaminants. It also refers to the etching process utilised in semiconductor fabrication, where the "cleaning" is the precision removal of thin layers of material.

Fortunately, a wide range of wet process equipment automation now exists that can more flexibly accommodate specific cleaning requirements. Modifying these automated cleaning tools to fit the application can cost-effectively enhance process repeatability, throughput, and safety. In many cases, only minor editing to the standard equipment is all that is necessary.

The benefits of automated cleaning equipment

"Companies that automate a cleaning process usually do so to improve process repeatability, production throughput or safety," says Louise Bertagnolli, president of JST Manufacturing. The company designs and manufactures a variety of manual to fully automated cleaning equipment, including systems that include all of the features and transfer devices required for a complete turnkey cleaning process.



Repeatability involves the ability to precisely repeat a cleaning process and is critical to maintaining

CODA-PIN

Subscriptions and Newsletters
Subscription to Engineering magazines
FREE newsletter
Test Probes & Test Jigs



Complete solutions
for process industries

Book your stand now

ONS 2020
31 AUG - 3 SEPT
STRAKER - NORWAY

DesignEngineer ADVANCES IN AUTOMATION DESIGN FOR AM BEST OF CONNECTORS

ProcessEngineer ADVANCES IN AUTOMATION DRILLING PRODUCTION STRATEGY PROTECTION STRATEGY

PowerEngineer PIONEERING IN PLANTS OIL & GAS SUBSEA SHOWCASE

Market Leading Engineering Magazines

FREE Subscription

Subscribe Now

Newsbrief

To receive our free weekly NewsBrief please enter your email address below:

To receive our free weekly NewsBrief please enter your email address below:

*

Please select your Country:

United Kingdom

Engineering Discipline:

Automotive

Aviation

- Design
- Electronics
- Mining
- Nuclear
- Oil & Gas
- Power
- Process
- Rail
- Renewables

Submit

[Read the latest NewsBrief](#)

quality. This includes exact measurement and dispensing of cleaning agents and rinsing solutions as well as providing the systems and tools needed to transport the cleaned items from one bath to another. Automating the cleaning process, of course, can increase production throughput for high-volume production. If the process takes place in a cleanroom, then the entire system including motors and robotics must be appropriate for that environment.

Since production can involve moving products around above hot tanks or near chemical baths, automating can improve safety as well. Similarly, it can improve production ergonomics, for example, by eliminating the need for employees to repeatedly rotate or handle the parts being processed, which reduces the potential for injury.

Maximising automated cleaning tools cost-effectively

Determining when to automate cleaning usually depends on the stage of development of the part or product. According to Bertagnolli, while a manual cleaning process is normally used during R&D, when the process is defined and the company has buying customers, it is a good idea to automate.

However, to successfully automate, it is often best to customise the cleaning systems to the specific needs of the application as much as possible. "When considering job modifications, it is important to take into account the requirements for floor space, product size, production throughput, etc.," says Bertagnolli. "Since one size does not fit all, it is crucial not to shove everybody into the same platform."

Bertagnolli cautions, however, that not every project needs to be fully customised from the ground up. Quite often, standard automation platforms can be customised according to length and height and number of baths. Cleaning process design engineers can consult with automation suppliers to determine where to put the transfer system and what automation modules will fit best in the space available.

"Unlike proprietary platforms that do not allow modification, the best platforms are tried and true, but offer a range of options that utilise the same motors, actuators, and automation in an interchangeable way," says Bertagnolli. "This allows flexibility while minimising cost and complexity."

This type of an approach can be successfully used in fully automated, special project, and semi-automated cleaning processes.

Fully automated cleaning stations

Semi to fully automated, multitask cleaning stations typically use at least four baths. Such stations can pick up and drop off product via robots at the baths as required, while following preprogrammed recipe sequences. However, the stations often need modification to operate most effectively.

To allow for modification, cleaning specialists such as JST offer multiple automation platforms that can accommodate various space constraints. The company can also tailor loading to the specific task by using front, rear, or overhead robots with either front or side loading. Optional turntables can enable ergonomic side loading as well as rear access for ease of maintenance as well. "For automated stations, the number of tanks, robot location, movement speed, loading, as well as sizing of everything is based on the specific requirements," says Bertagnolli.

In regards to modifying such automated cleaning systems, the company works closely with automation partners such as Bosch Rexroth to develop cleaning stations using linear motion and electric drive and control technology. Recently, the two firms worked together to create an automated system for cleaning silicon chunks to the extreme purity of 11N to meet requirements for the manufacture of semiconductor chips. The project entailed building a cleaning line 138ft in length and incorporating multiple gantry robots.

The throughput volume requirement for the chunks was four tons for every 22-hour shift. To accomplish this, JST had to develop a unique basket system to transport the material throughout the process.

To provide for such a long cleaning system, JST engineered and built it in two units. In the 24ft-long unit, baskets of chunks are manually loaded through an auto-door. Then two-axis robots cycle the baskets through five acid etch baths and two rinse baths arranged in a single row down the length of the second unit.

Special automated cleaning projects

When automated cleaning and stripping of wafers, optics, disc drives, flat panels and other delicate parts is required for special projects, equipment is available that operates on a completely self-contained, dry-to-dry basis. One such unit is JST's 300 CLV Cleaner and Stripping Tool. Once product is placed in the dry tank, the unit can process through either single or multiple chemical processes, rinse and dry according to a pre-programmed recipe without operator intervention or mechanical moving parts to maintain.

As an example, the National Ignition Facility (NIF) at Lawrence Livermore National Laboratories (LLNL) has used such a tool. NIF, the world's highest-energy laser system – a stadium-size machine – consists of 192 laser beams that will focus nearly two million joules of energy and create temperatures and pressures that exist in the cores of stars and giant planets.

One of the innovations in the NIF cleaning tool – used in a tank-like configuration and designed to clean up to 300-pound laser optics – was eliminating the need to move the optics to different locations in order to perform the washing, rinsing and drying functions. "Our engineers suggested that rather than transport these heavy optics for such functions, we could simply transport the chemistry (solutions) to the optics in a fixed location," explains Bertagnolli. "We also designed a sling-like device to hold the optics and also let technicians rotate them during the inspection process."

JST built two cleaning tools for NIF, which are mirror images for the same price a traditional linear transfer tool could be built. This affords NIF double the capacity and most important, provides redundancy.

Semi-automated cleaning systems

Many processors with lower-volume throughput requirements might consider using semi-automated cleaning systems. Compared to manual systems, these provide better repeatability, faster production and added safety. This type of cleaning system is appropriate for MEMs, LEDs and silicon applications. It is compact, software controlled, and usually easy to service.

JST manufactures a standard compact semi-automated wet bench called the Tigress, a two axis, front-to-back compact system that is used by smaller semiconductor companies. A dual version of this semi-automatic system is also available. It is popular among semiconductor manufacturers that use it for cleaning, stripping and etching of semiconductor substrates when cleaning acids, bases or solids are used to remove photoresists. "Although design engineers may be resigned to using standard, automated, wet process cleaning equipment, tailoring options to the project can significantly enhance quality, production, and safety while actually cutting cost," concludes Bertagnolli